

MP-WU5603

Introducing Our Very Latest
SSL 3LCD Projector



PJLink™

CRESTRON

HDBT™

Laser

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE

AMX

3LCD

Introducing our innovative 3LCD MP-WU5603 projector which combines all our technical expertise with our market leading knowledge.

This new, portable projector can produce 6,000 ANSI, has a 1,500,000:1 contrast ratio, a resolution of 1920 x 1200 and will provide 20,000 hours of maintenance-free operation.

So whatever the situation, our MP-WU5603 projector is the perfect solution for today's professionals. It combines simple usability with powerful performance in a lightweight and compact design, enabling users to set it up and get working in seconds.

Key Features:

WUXGA 1920 x 1200 resolution

6,000 ANSI lumens white / colour output

1,500,000:1 contrast ratio

Images up to 300" diagonal

Lens Shift and HDBase T

20,000 hrs / 5 year warranty (whichever comes first)

Please note: This is a preliminary data sheet. Content, technical specifications and images are subject to change.

MP-WU5603 3LCD Laser Projector

Technical Specifications

Panel Size	3LCD 16mm (0.64")	Digital Input	HDMI x 2 (HDCP compliant, HDMI 1 shared with MHL) HDBaseT x 1
Panel Structure	3LCD	Analogue Input	15-pin Mini-D-Sub x 2, RCA Jack x 1
Resolution	WUXGA (1920 x 1200)	Video Output	15 pin Mini D-Sub x 1 (shared with analog computer input)
Light Output (Brightness) ANSI Lumens	6,000 (Normal)	Audio Input	3.5mm Stereo Mini Jack x 2, RCA Jack (L/R) x 1
Contrast Ratio	1,500,000:1	Audio Output	3.5mm Stereo Mini Jack x 1
System (Hours)	20,000	RS-232C Control	1 x 9-pin D-Sub
Lens	Built-in	Wireless LAN	USB-WL-5G wireless adaptor (optional)
Lens Zoom	Manual Zoom x 1.7	Wired LAN	RJ45 connector x 1
Lens Shift	Manual Lens Shift	USB Type-A	USB Type A x 1 (wireless adapter)
Lens Focus	Manual focus	USB Type B	USB Type B x 1 (for service use)
Lens Shift	Vertical 0 – +56.5% Horizontal +/-4.6%	Power Supply	AC 100V – 120V / AC 220V – 240V (50/60Hz)
Projection Lens F Number	1.58 – 2.06	Operating Power Consumption	400W
Focus Distance	0.9 – 9.2 m (Wide), 1.5 – 15.8 m (Tele)	Standby Power Consumption	Less than 0.5W
Throw Distance	0.413m - 0.903m (centre of glass to screen)	Weight	8.5Kg
Distance to Width Ratio/ Throw Ratio (:1)	1.4 – 2.4	Dimensions (W x H x D)	506 x 136 x 424mm
Diagonal Display Size	30 – 300"	Noise (Normal)	36dB (Normal), 27dB (Whisper)
Installation	Ceiling, Tabletop, Rear, Portrait, 360° Projection	Filter Life (Hours)	20,000 Hours
Speakers	16W mono	Certification	CE Marking, EN61000-3-2, EN61000-3-3, EN55032 (Class A), EN55035 (EMC Directive), EN60950-1 (Low Voltage Directive), WEEE/RoHS compliant
Digital Keystone Correction (Degrees)	Horizontal ± 30°, Vertical ± 30°	Computer	IBM Compatible VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, UXGA, WUXGA
Picture Modes	Standard, Natural, Cinema, Dynamic, Whiteboard, DICOM SIM, User-1, User-2, User-3	Video	525i (480i), 525p (480p), 625i (576i), 625p (576p), 1125i (1080i@50/60), 1125p (1080p@50/60), 4K (3840x2160@30 4:4:4, Compressed)
Picture Adjustments	ASPECT selection (Normal/4:3/16:9/16:10/14:9/Zoom/Native), Perfect Fit (4 corners and 4 sides), Frame Lock (Data signal with vertical frequency of 49 to 51Hz, 59 to 61Hz), HDCR, Image blank by RS232C/Remote control, Image optimizer, Magnify, Mirror reverse image, Up-side down image	Supplied Accessories	Power Cable (1.8m), Computer Cable (2m), Remote Control Unit x 1, Concise User Manual x 1, Security Label x 1, Hook Metal x 1, Screw x 1, HDMI Cable Holder (x 2), Cable Tie (Large x 1, Medium x 2), AA Batteries x 2, Lens Cover x 1
Operating Features	Keystone V/H, PerfectFit, Standby audio, Audio pass through, Cloning function, Easy schedule setting, Auto power on	Optional Accessories	USB wireless adaptor USB-WL-5G
Network Features	Wireless Capability(Optional), Multi Projector, Moderator Control Mode, Projector Quick Connection (iOS / Android app), Projector Monitoring and Control from a Remote Location, E-mail Alerts	Filter	UX43581
Security Features	Password/Myscreen Password, Pin Lock, Key Lock	Remote Control	HL03037
Supported Languages	34 Languages (English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Arabian, Persian, Czech, Danish, Hungarian, Romanian, Slovenian, Croatian, Greek, Lithuanian, Estonian, Latvian, Thai, Portuguese (Brazil), Indonesian, Vietnamese, Hebrew)	Projector/ Light source Warranty	20,000 hours / 5 years (whichever comes first) (for extended warranties please contact your local dealer)



Dealer Stamp

maxell
Within the Future

Hitachi Digital Media
Hitachi Europe Ltd, Whitebrook Park, Lower Cookham Road,
Maidenhead, Berkshire SL6 8YA, United Kingdom
Tel: +44 (0)1628 585 000 / Fax: +44 (0)1628 585 163